



| Bezeichnung | Hauptabmessungen (mm) | | | | | Grundlegende Belastungswerte | |
|-------------|-----------------------|-----|------|------|------|------------------------------|----------|
| | D | D | B | C | T | Dynamisch | Statisch |
| d90L | 90 | □ | 10 | □ | □ | 24.8 | 28 |
| d160 | 160 | □ | 26.5 | □ | □ | 101.1 | 124.9 |
| d240 | 240 | □ | 24.1 | □ | □ | 209.6 | 290.5 |
| SE140 | 110 | 140 | 15 | 12 | 16 | 31.2 | 36.3 |
| SE140/YA | 110 | 140 | 15 | 12 | 16 | 35.5 | 44.1 |
| SE170 | 136 | 170 | 13 | 13 | 19.5 | 31.2 | 39.1 |
| SE18D | 145 | 180 | 20 | 19 | 21 | 56.1 | 72.5 |
| SE185 | 145 | 185 | 22 | 20 | 22 | 41.4 | 52.5 |
| SE195 | 155 | 195 | 15 | 15 | 20 | 65.1 | 86.9 |
| SE210 | 165 | 210 | 16.8 | 19 | 22 | 72.4 | 98 |
| SE225 | 180 | 225 | 16.5 | 18 | 21.5 | 74.6 | 105 |
| SE235 | 180 | 235 | 20.9 | 25 | 26.3 | 117.5 | 154.5 |
| SE250 | 200 | 250 | 23 | 20.5 | 24 | 168 | 285 |
| SE276 | 220 | 276 | 18 | 26 | 26 | 114.5 | 164 |
| SE295 | 220 | 295 | 25.5 | 25.5 | 33 | 201.1 | 265.9 |
| SE310 | 230 | 310 | 27 | 27 | 38 | 214 | 290 |
| SE313 | 246 | 313 | 22 | 22 | 32 | 180 | 270 |
| SE330 | 250 | 330 | 27 | 27 | 38 | 212.8 | 299 |
| SE360 | 250 | 360 | 36 | 34 | 44 | 319.5 | 467 |
| SE370 | 280 | 370 | 27 | 22 | 40 | 228.7 | 335.9 |

Construction machinery bearings

| | | | | | | | |
|----------|-------|-----|------|------|------|-------|-------|
| SE400 | 280 | 400 | 39 | 37 | 48 | 365.5 | 575.2 |
| SE402 | 304.8 | 402 | 50.8 | 38 | 50.8 | 305 | 488 |
| SE420 | 280 | 420 | 37 | 37 | 48 | 385.5 | 618.3 |
| SE423 | 330 | 423 | 50 | 38 | 50 | 294 | 480 |
| AC130166 | 130 | 166 | 4 | 14 | 18 | 52.5 | 68.4 |
| AC135170 | 135 | 170 | 15 | 20 | 20 | 53.9 | 71.7 |
| AC150182 | 150 | 182 | 12 | 16 | 16 | 47.3 | 65.4 |
| AC220300 | 220 | 300 | 28 | 28 | 35 | 206.1 | 270.6 |
| AC300370 | 300 | 370 | 28.5 | 28.5 | 33 | 209.8 | 320.4 |
| DE166 | 130 | 166 | 12X2 | 30.5 | 35.5 | 72.1 | 114.4 |